



# vulcan® 714 Master

## Key performance

- Long blanket lifetime
- High print quality
- Calibrated thickness
- Positive paper feed

## MAIN APPLICATION

Commercial Web Heatset

**Vulcan 714 Master is available in 3-ply, (1,71 mm) thickness.**



**714 Master**

## ✓ The product at a glance

|                                                           |                                                                                                                                          |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>INK COMPATIBILITY</b>                                  | Conventional                                                                                                                             |
| <b>PRINTING SURFACE COLOUR</b>                            | Light Blue                                                                                                                               |
| <b>THICKNESS (mm)</b>                                     | 1,71                                                                                                                                     |
| <b>AVERAGE LOAD VALUE<br/>N/cm2 @ 0,23 mm Indentation</b> | 250                                                                                                                                      |
| <b>SURFACE ROUGHNESS<br/>(Ra micron)</b>                  | 1,0                                                                                                                                      |
| <b>FEED FEATURES</b>                                      | Positive                                                                                                                                 |
| <b>ELONGATION (%)</b>                                     | <0,9                                                                                                                                     |
| <b>TENSILE STRENGTHS (N/mm)</b>                           | >60                                                                                                                                      |
| <b>WATER &amp; SOLVENT PROTECTION</b>                     | Yes                                                                                                                                      |
| <b>ADDITIONAL INFORMATION</b>                             |                                                                                                                                          |
| <b>BLANKET CONSTRUCTION</b>                               | The micro ground surface combined with a robust carcass construction results in a calibrated blanket thickness with a minimal relevance. |

**FOR ANY FURTHER DETAILS AND FOR A QUOTATION  
PLEASE REFER TO YOUR SALES MANAGER  
OR EMAIL US AT: [printing@trelleborg.com](mailto:printing@trelleborg.com)**