

## vulcan Kart-One

## Key performance

- The most compressible blanket specifically designed for packaging applications
- High smash resistance plus superb print quality, ink transfer and cost efficiency during the print run
- Sizes are available to suit any packaging press format
- Edge marking resistant
- Increased blanket lifetime

## MAIN APPLICATION

Packaging

Vulcan Kart-One is available in 3-ply (1,96 mm) thickness.





Vulcan Kart-One

Vulcan Kart-One UV

## The product at a glance

INK COMPATIBILITY	Hybrid
PRINTING SURFACE COLOUR	Dark Blue
THICKNESS (mm)	1,96
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	150
SURFACE ROUGHNESS (Ra micron)	0,6
ELONGATION (%)	<0,9
TENSILE STRENGHTS (N/mm)	>60
WATER & SOLVENT PROTECTION	NO
ADDITIONAL INFORMATION	
SUBSTRATES	Exceptional with cardboard

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printing@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.